

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

General

In-line four stroke diesel engine with direct injection. Rotation direction, anti-clockwise viewed towards flywheel.
Turbocharged

Number of cylinders			6
Displacement, total		litre in ³	16,12 983,9
Firing order			1-5-3-6-2-4
Bore		mm in	144 5,67
Stroke		mm in	165 6,50
Compression ratio			16,5:1
Dry weight	Engine only, excluding cooling system	kg	1700
		lb	3748
	GenPac	kg	2200
		lb	4850
Wet weight	Engine only, excluding cooling system	kg	1770
		lb	3902
	GenPac	kg	2370
		lb	5225

Performance

		r/min	1500	1800
Prime Power	without fan	kW hp	553 752	615 836
	with fan	kW hp	536 729	585 796
Standby Power	without fan	kW hp	613 834	674 917
	with fan	kW hp	596 811	644 876
	without fan	kW hp		
	with fan	kW hp		
Torque at:	Prime Power	Nm lbft	3521 2596	3263 2406
	Standby Power	Nm lbft	3902 2878	3576 2637
Mean piston speed		m/s ft/sec	8,3 27,1	9,9 32,6
Effective mean pressure at:	Prime Power	MPa psi	2,7 398	2,5 369
Effective mean pressure at:	Standby Power	MPa psi	3,0 441	2,8 404
Max combustion pressure at:	Prime Power	MPa psi	18,8 2727	19,6 2843
Max combustion pressure at:	Standby Power	MPa psi	20 2901	19,8 2872
Total mass moment of inertia, J (mR ²)		kgm ² lbft ²	4,20 99,7	
Degree of irregularity at:	Prime Power		1:33	1:55
	Standby Power		1:29	1:51
Friction Power		kW hp	38 51,68	55 74,8

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Derating

The engine may be operated up to 1500m without derating.

For operating at higher altitudes the power will be derated according to the graph below.

There is no derating for ambient temperature or humidity.

Engine noise emission

Test Standards: ISO 3744-1981 (E) sound power (without fan, intake and exhaust noise)

Tolerance ± 0.75 dB(A)

		r/min	1500	1800
Measured sound power L _w	No load	dB(A)	113	117
	Prime Power	dB(A)	117	120
	Standby Power	dB(A)	117	120
Calculated sound pressure L _p at 1 m	No load	dB(A)	101	105
	Prime Power	dB(A)	105	108
	Standby Power	dB(A)	105	108

Unsilenced exhaust noise

Data calculated as sound pressure L_p.

Assumed microphone distance 1 m

	r/min	1500	1800
Prime Power	dB(A)	116	120
Standby Power	dB(A)	117	120

Test conditions for load acceptance data

Warm engine.	Generator	Model	Type of AVR
	Stamford	HCI534F1	MX341

Load acceptance performance can vary due to actual alternator inertia, voltage regulator, type of load and local ambient conditions.

Single step load performance at 1500 rpm

Load (%)	Speed diff (%)		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	2,8		1,8		20-100	11,6		3,7	
0-40	5,6		1,9		40-100	7,3		2,7	
0-48	7,0		2,6		48-100	6,3		2,1	
0-60	8,8		2,8		60-100	5,5		1,9	
0-65	10,0		3,1		65-100	4,6		1,5	
0-80	13,6		4,0		80-100	3,1		1,5	
0-100	18,7		5,5						
100-0	8,8		2,4						
0-20		3,2		1,9	20-98		12,5		9,2
0-40		6,3		2,1	40-98		7,5		9,0
0-44		7,0		2,7	44-98		7,0		7,8
0-59		10,0		3,3	59-98		5,8		4,3
0-60		10,2		3,4	60-98		5,7		3,9
0-80		15,9		4,5	80-98		3,0		1,6
0-98		20,4		8,8					
98-0		9,1		2,4					

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Single step load performance at 1800 rpm

Load (%)	Speed diff %		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	1,6		1,4		20-100	7,3		2,2	
0-40	3,6		1,5		40-100	4,8		2,0	
0-60	5,5		1,7		60-100	3,7		1,6	
0-69	7,0		1,8		69-100	2,9		1,3	
0-80	8,6		2,0		80-100	1,8		1,3	
0-86	10,0		2,0		86-100	1,2		1,2	
0-100	11,9		2,0						
100-0	5,8		2,6						
0-20		1,8		1,5	20-99		7,7		14,8
0-40		4,0		1,7	40-99		5,5		11,2
0-60		6,2		1,8	60-99		3,8		4,4
0-64		7,0		1,8	64-99		3,6		4,3
0-79		10,0		1,9	79-99		1,8		1,4
0-80		10,2		1,9	80-99		1,7		1,3
0-99		13,5		8,1					
99-0		6,6		2,6					

Cold start performance

Cold start performance		r/min	1500	1800	
Time from start to no load speed at ambient temperature:	°C	20	s	4,2	6,0
		5	s	6,8	7,7
		-15*	s	4,8	5,7
Time from start to stay within 0.5% of no load speed at ambient temperature:	°C	20	s		
		5	s		
		-15*	s		

* With manifold heater 4 kW engaged, lubrication oil 15W/40 and block heater.

Block heater type	Make	Power kW	Engaged hours	Cooling water temp engine block
	Volvo Penta no:889858	2000W	10h	16°C 61°F

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Lubrication system		r/min	1500	1800
Lubricating oil consumption	Prime Power	litre/h US gal/h	0,10 0,026	0,10 0,026
	Standby Power	litre/h US gal/h	0,11 0,029	0,11 0,029
Oil system capacity including filters		litre US gal	48 12,7	
Oil sump capacity:	max	litre US gal	42 11,1	
	min	litre US gal	32 8,5	
Oil change intervals/specifications:	VDS-2/VDS-3*		h	600
	VDS, ACEA, E3*		h	400
	ACEA E2, API CD, CF, CF-4, CG-4*		h	200
Engine angularity limits:	front up		°	30
	front down		°	30
	side tilt		°	30
Oil pressure at rated speed		kPa psi	300 - 650 44 - 94	
Oil pressure shut down switch setting		kPa psi		
Lubrication oil temperature in oil sump:	max	°C °F	130 266	
Oil filter micron size		μ	0,040	

* See also general section in the sales guide

Fuel system		r/min	1500	1800
Prime Power Specific fuel consumption at:	25%	g/kWh	215	224
		lb/hph	0,349	0,363
	50%	g/kWh	196	201
		lb/hph	0,318	0,326
	75%	g/kWh	196	197
		lb/hph	0,318	0,319
	100%	g/kWh	199	202
		lb/hph	0,323	0,327
Standby Power Specific fuel consumption at:	25%	g/kWh	210	220
		lb/hph	0,340	0,357
	50%	g/kWh	195	200
		lb/hph	0,316	0,324
	75%	g/kWh	196	198
		lb/hph	0,318	0,321
	100%	g/kWh	200	204
		lb/hph	0,324	0,331

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Fuel system	r/min	1500	1800
Fuel to conform to	ASTM-D975-No1 and 2-D JIS KK 2204, EN 590		
System supply flow at:	litre/h US gal/h	190,0 50,2	210,0 55,5
Fuel supply line max restriction	kPa psi	10,0 1,5	10,0 1,5
Fuel supply line max pressure, engine stopped	kPa psi	0,0 0,0	0,0 0,0
System return flow	litre/h US gal/h	25,0 6,6	25,0 6,6
Fuel return line max restriction	kPa psi	20,0 2,9	20,0 2,9
Maximum allowable inlet fuel temp	°C °F	60 140	60 140
Prefilter / Water separator micron size	μ	0,010	
Fuel filter micron size	μ		
Governor type/make, standard	Volvo / EMS 2		
Injection pump type/make	Delphi / E3		
Injection timing std.	°B.T.D.C		
Injection timing	°B.T.D.C		

Intake and exhaust system			r/min	1500	1800
Air consumption at: (+25°C and 100kPa)	Prime Power		m ³ /min cfm	43,65 1541	53,07 1874
	Standby Power		m ³ /min cfm	46,96 1658	54,85 1937
Max allowable air intake restriction including piping			kPa psi	5 0,7	5 0,7
Air filter type			Single stage paper cartridge		
Air filter cleaning efficiency			%	99,85	
Heat rejection to exhaust at:	Prime Power		kW BTU/min	415 23601	472 26842
	Standby Power		kW BTU/min	463 26330	530 30141
Exhaust gas temperature after Low Pressure turbine at:	Prime Power		°C °F	450 842	422 792
	Standby Power		°C °F	463 865	461 862
Max allowable back pressure in exhaust line			kPa psi	10 1,5	10 1,5
Exhaust gas flow at: (temp and pressure after turbine at the corresponding power setting)	Prime Power		m ³ /min cfm	101,6 3588	119,0 4202
	Standby Power		m ³ /min cfm	111,8 3948	130,1 4594

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Cooling system		r/min	1500	1800
Heat rejection radiation from engine at:	Prime Power	kW BTU/min	23 1308	26 1479
	Standby Power	kW BTU/min	33 1877	33 1877
Heat rejection to coolant engine radiator at:	Prime Power	kW BTU/min	208 11829	246 13990
	Standby Power	kW BTU/min	226 12852	270 15355
Heat rejection to coolant CAC radiator at:	Prime Power	kW BTU/min	116 6597	121 6881
	Standby Power	kW BTU/min	125 7109	135 7677
Coolant	Volvo Penta coolant "ready mix" or Volvo Penta coolant mixed with clean fresh water 40 / 60.			
Radiator cooling system type		Closed circuit		
Engine radiator core area		m² foot²	1,68 18,08	
CAC radiator core area		m² foot²	1,68 18,08	
Fan diameter		mm in	965 37,99	
Fan power consumption		kW hp	17 23	30 41
Fan drive ratio			1,04:1	
Coolant capacity,	engine	litre US gal	33 8,72	
	Engine radiator and CAC radiators with hoses	litre US gal	95 25,10	
Coolant pump		drive/ratio	Belt / 1,85:1	
Coolant flow engine radiator (at fully open thermostat)		l/s US gal/s	4,8 1,27	6,0 1,59
Coolant flow CAC radiator (at fully open thermostat)		l/s US gal/s	1,5 0,40	1,6 0,42
Coolant pressure drop over engine-radiator incl. piping		kPa psi	34 4,9	50 7,3
Coolant pressure drop over CAC-radiator incl. piping		kPa psi	24 3,5	25 3,6
Coolant pressure drop over complete cooling system		kPa psi	87 12,6	105 15,2
Thermostat	start to open	°C °F	82 180	
	fully open	°C °F	92 198	
Maximum static pressure head (expansion tank height + pressure cap setting)		kPa psi	100 14,5	
Minimum static pressure head (expansion tank height + pressure cap setting)		kPa psi	70 10,2	
Standard pressure cap setting		kPa psi	75 10,9	
Maximum top tank temperature		°C °F	103 217	
Draw down capacity	4% of total cooling system capacity			

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Charge air cooler system		r/min	1500	1800
Heat rejection to charge air coolers	Prime Power	kW	125	156
		BTU/min	7109	8872
	Standby Power	kW	142	180
		BTU/min	8075	10236
		kW		
		BTU/min		
Charge air mass flow	Prime Power	kg/s	0,86	10,5
	Standby Power	kg/s	0,93	10,9
		kg/s		
Charge air inlet temp. (Charge air temp after turbo compressor)	Prime Power	°C		
		°F		
	Standby Power	°C		
		°F		
		°C		
		°F		
Charge air temperature. Inlet manifold, max allowed. (At air inlet temp. 25 degr. C)	Prime Power	°C		
		°F		
	Standby Power	°C	50	50
		°F	122	122
		°C		
		°F		
Maximum pressure drop over charge air cooler incl. piping		kPa		
		psi		
Charge air pressure (After charge air coolers)		kPa	462	462
		psi	67,01	67,01
Standard charge air cooler core area		m ²		
		foot ²		

Cooling performance

Cooling air flow and external restriction at different radiator air temperatures based on 103°C TTT and 50% antifreeze (radiator and cooling fan, see optional equipment)

Engine speed rpm	Air on temp °C	PRIME POWER		STANDBY POWER	
		Air flow kg/s	External restriction Pa	Air flow kg/s	External restriction Pa
1500	33			8,0	1000
	39	8,0	1000		
	43			10,0	600
	49	10,0	600		
	50			12,0	200
	54			13,0	0
	55	12,0	200		
1800	58	13,0	0		
	35			10,0	1000
	42	10,0	1000		
	44			12,0	600
	50			14,0	200
	51	12,0	600		
	55			15,0	0
	56	14,0	100		
	58	15,0	0		

Note! Calculated values >0 Pa

VOLVO PENTA TWD 1643GE	Document No 21117581	Issue Index 01
---	--------------------------------	--------------------------

Engine management system

Functionality	Alternatives	Default setting
Governor mode	Isochronous / droop	Isochronous
Governor droop	0-8%	4%
Governor response	Adjustable PID-constants (VODIA)	Not adjusted
Dual speed	1500 / 1800	According to customer
Idle speed	600-1200	900
Fine speed adjustment	±120	0,0
Stop function	Energized to Run / Stop	Energized to Stop
Preheating function	On / Off	Off
Lamp test	On / Off	On

Engine protection		Alarm level		Engine protection	
Parameter	Unit	Setting range	Default setting	Level	Action. Default/Alternative
Oil temp	°C	120 - 130	125	Setting +5	Shut down. ON/OFF*
Oil pressure	Low idle	kPa	-	190	Shut down. ON/OFF*
	1500 rpm	kPa	-	250	Shut down. ON/OFF*
	1800 rpm	kPa	-	300	Shut down. ON/OFF*
Oil level		-	Min level	-	
Piston cooling pressure >1000 rpm	kPa	-	150	150	Shut down. ON/OFF*
Coolant temp	°C	95 - 103	98	Setting +5	Shut down. ON/OFF*
Coolant level		See cooling system	On	Low level	Shut down. ON/OFF*
Fuel feed pressure	Low idle	kPa	150		-
	>1400 rpm		250		-
Water in fuel		-	High level	-	-
Crank case pressure	kPa	-	Increased pressure	Increased pressure	Shut down. ON/OFF*
Air filter pressure droop	kPa	-	5,0	-	-
Engine protection		Alarm level		Engine protection	
Altitude, above sea	m	-	-	1500	Automatic derating, see section derating
Charge air temp	°C	-	80	85	Shut down. ON/OFF*
Charge air pressure	kPa	-	500 (absolute)	510 (absolute)	Shut down. ON/OFF*
Engine speed	rpm	100 - 120% of rated speed	115% of rated speed	Alarm level	Shut down. ON/OFF*
Exhaust temp**	°C	-	610	640	Shut down. ON/OFF*
Low voltage	V	-	25,5	-	-

* Off means no shut down, alarm only

** Between high pressure turbin and low pressure turbin

VOLVO PENTA TWD 1643GE	Document No	Issue Index
	21117581	01

Electrical system		r/min	1500	1800
Voltage and type		24V / insulated from earth		
Alternator:	make/output	Amp	Bosch / 80	
	tacho output	Hz/alt. Rev	6	
	drive ratio		3,9 : 1	
Starter motor	make		Melco	
	type		105P70	
	kW		7,0	
Starter motor solenoid:	pull current	Amp	-	
	hold current	Amp	2,3	
Number of teeth on:	flywheel		153	
	starter motor		12	
Max wiring resistance main circuit		mΩ	-	
Inrush current at +20°C		Amp	750	
Cranking current at +20°C		Amp	300	
Crank engine speed at 20°C		rpm	155	
Starter motor battery capacity:	max	Ah/A	2x225	
	min at +5°C	Ah/A	-	
Inlet manifold heater (at 20 V)		kW	4,0	
Power relay for the manifold heater		Amp	1	

Power take off		r/min	1500	1800
Front end in line with crank shaft max:		Nm lbft	-	
Front end belt pulley load. Direction of load viewed from flywheel side:	max left	kW hp	-	-
	max down	kW hp	-	-
	max right	kW hp	-	-
Timing gear at compressor PTO max:		Nm lbft	160 118	
Speed ratio direction of rotation viewed from flywheel side		1,31:1/ anti-clockwise		
Timing gear at servo pump PTO max:		Nm lbft	100 74	
Speed ratio direction of rotation viewed from flywheel side				
Timing gear at hydraulic pump PTO max:		Nm lbft	-	
Speed ratio direction of rotation viewed from flywheel side				
Max allowed bending moment in flywheel housing		Nm lbft	15000 11063	
Max. rear main bearing load		N lbf	NA	